

STANDARDS FOR SPRAYED POLYURETHANE FOAM

Old Standards:

- CAN/CGSB-51.23M, Sprayed- Applied Rigid Polyurethane Cellular Plastic Thermal Insulation.
- CAN/CGSB-51.39-M92, The Installation of Spray Foam-in-Situ Urethane Insulation for Residential Building Construction.

New Standards:

- CAN/ULC-S705.1-01, including amendment 1&2, Standard for Thermal Insulation - Sprayed- Applied Rigid Polyurethane Foam – Medium Density – Material Specification.
- CAN/ULC-S705.2-05, Standard for Thermal Insulation – Spray Applied Rigid Polyurethane Foam – Medium Density, Application.

These Standards may be obtained from:

Underwriters Laboratories Canada (ULC)
7, Crouse St.
Scarborough
Ontario, M1R-3A9
Tel: 416-757-3611
Fax: 416-757-8915

TECHNICAL ASSISTANCE

For more detailed information, call:

Eastern region

Ontario, Quebec, Maritimes

Toll-Free: 1-866-474-3538

Western region

British Columbia, Alberta, Saskatchewan, Manitoba,
North Western Territories, Yukon, Nunavut

Toll-Free: 1-800-891-0671

www.walltiteco.com
